



# Enelion Stilo

## Technical specifications

|                                       |   |
|---------------------------------------|---|
| Body                                  | Weatherproof, anodised aluminium              |
| Protection against intrusion          | IP 54   |
| Impact protection                     | IK10  |
| Current protector*                    | RCD B / Enelion RCM B + RCD A                 |
| Charging connector                    | AC Type 2; charging cable length 5 m; EN      |
| Energy Meter                          | 62196-1 built-in                              |
| Maximum energy meter*                 | Installed in the intermediate box             |
| Communication module Bridge OCPP 1.6* | Installed in the intermediate box             |
| User environment                      | Offline / WiFi, Ethernet / LTE (GSM)          |
| User authorization*                   | RFID + 2 cards (MIFARE / ISO14443), no charge |
| Charge point parameters               | Three-phase                                   |
| Voltage in the network                | 400 V   |
| Charge point frequency                | 50 Hz   |
| Charging current/power                | 3× 32 A / 22 kW                               |
| Charging voltage                      | 3× 230 V AC                                   |
| Logo: laser engraved logo*            | According to customer requirements            |
| Operating temperature                 | -25 °C / +55 °C                               |
| Storage temperature                   | -40 °C / +80 °C                               |
| Maximum height above sea level        | 2 000 m                                       |
| Height                                | 430 mm  |
| Width                                 | 185 mm  |
| Depth                                 | 56 mm   |
| Weight                                | 3.0 kg – 3.5 kg                               |

\*Optional accessories